


接线图/WIRING DIAGRAM



步距角/STEP ANGLE	1.8° \pm 5%
相数/NO. OF PHASES	2
电压/RATED VOLTAGE	3.6 V
电流/RATED CURRENT	6.0 A
电阻/RESISTANCE	0.55 ohm \pm 10% AT 20° C
电感/INDUCTANCE	8.4 mH \pm 20% AT 1kHz, 1Vrms
静转矩/HOLDING TORQUE	1200 N.cm以上/MIN.
定位转矩/DETENT TORQUE	24.5 N.cm以下/Max
转动惯量/ROTOR INERTIA	4000g.cm ²
引出线规格/LEAD STYLE	AWG18 UL1007
绝缘等级/INSULATION CLASS	CLASS B
绝缘耐压/DIELECTRIC STRENGTH	500V A.C 1分钟/MINUTE
绝缘电阻/INSULATION RESISTANCE	100 M Ω 以上/MIN.
允许轴向负载/ALLOW AXIAL LOAD	60 N
允许径向负载/ALLOW RADIAL LOAD	220 N (轴端/ON THE SHAFT END)

备注/(NOTE):

技术部
2020.04.20
张建伟

				技术规格书		SYS MOTOR	
				TECHNICAL SPECIFICATION			
A	2020.04.20	----	翻新	COW	一般公差 TOLERANCE $\pm 0.3/\pm 0.3^\circ$		
版本 REV.	年月日 DATE	变更番号 ECN.	变更内容 REVISIONS	设计 BY	比例 SCALE	1:1	三视图 THIRD ANGLE PROJECTION
制图/DRAWING				Allen	2016.11.10	型号 MODEL	34HS5460D14L40-J5-25
设计/DESIGNED				Allen	2016.11.10		
审核/CHECKED				ANDY	2016.11.10		
批准/APPROVED						单位 UNIT	mm
						页 SHEET	1/1